

- Network DVR -
 Tack Care your family Anytime , anywhere

Products Ovreview

[Home](#) > [Products Ovreview](#) > [H.264 Network DVR](#) > [H.264 Hexaplex 9/16 CH Network DV](#)

▶ Digital Video Recorder

MPEG-2 Network DVR

H.264 Network DVR

M-JPEG Network DVR

▶ Wireless Security

H.264 Hexaplex 9/16 CH Network DVR

[Back](#)


Model:KW36299-36296

Features :

- 16 / 9 CH H.264 DVR with sixfold operation record, live, playback, backup, control, & remote access
- H.264 Baseline Profile video compression/decompression with configurable quality
- Realtime live display, 30 (NTSC) / 25 (PAL) IPS for each channel
- Bi-directional audio capabilities
- Audio in 4 CH / audio out 2 CH
- Ethernet for remote access, including web access, e - mail alarm notification and software upgrade
- I.E. software for up to 4 DVRs
- USB 2.0 for video/audio backup to versatile USB2.0 storage devices
- Internal DVD Models: Video/audio backup to internal DVD, including DVD + RW, DVD + R, and DVD - R
- 1 IR remote controller can control up to 4 DVRs
- Dust filter for harsh environments
- Multi - lingual support for setup and display
- Open system architecture for ease of access via network, RS - 485 keyboard

Specifications

Item	KW3629	KW36296
Channel	9CH	16CH
Video Input Format	NTSC / PAL : BNC 9CH In / 2CH Out	NTSC / PAL : BNC 16CH In / 2CH Out
Display Resolution	NTSC : 720 x 480 fps ; PAL: 720 x 576fps	
Recording Frame Rate	NTSC : 60/720 x 480,120/720 x 240,240 / 360 x 240.	
& Resolution	PAL : 50/720 x 576,100/720 x 288,200 / 360 x 288	
Compression Method	Video : H.264 Audio : ADPCM	
Hard Disk Capacity	Over 500G Bytes , SATA HDDs x 4 or SATA HDDs x 2 & IDE HDDs x 2	
Recording Time	23 days with 500GB HD @ 25 fps for Continuous Recording mode	
Recording Mode	Continuous, Motion detection, Sensor activated, Time schedule	
Sensors, Alarm	9 Input, 2 Output	16 Input, 2 Output
Audio	4CH In , 2CH Out	
Network	RJ - 45	
Backup	2 USB 2.0 ports for USB 2.0 disk drives, DVD + RW, DVD + R, DVD - R, card readers, HDD, etc. Internal DVD models: DVD + RW, DVD + R, DVD	
PTZ	RS - 232 / RS - 485	
IR Remote Control Unit	Yes	
VGA output	Optional	
Power Supply	90 ~ 264 VAC 47 ~ 63Hz, 110W Max	
Operating Temperature	0° ~ + 45°	

[^](#) [TC](#)

[| About us](#) | [Products](#) | [News](#) | [Job Opportunities](#) | [Contact us](#)



KINGWAVE TECHNOLOGY CO.,LTD.

18F-3, No. 186, Jian-Yi Road, Chung-Ho City, Taipei, Taiwan TEL:+886-2-8227-1868 FAX:+886-2-8227-1878