

# EAT•N

# Powerware

## Powerware 3105 Uninterruptible Power System

Product Focus

350-700 VA power protection for small office and home office applications



### Product Snapshot

**Power Rating:** 350-700 VA  
**Voltage:** 240 VAC  
**Frequency:** 50 Hz  
**Configuration:** Low profile, plug-and-play unit  
**Topology:** Standby

### Features

- Protect small office and home office equipment from power outages, surges and sags.
- Save space with a compact design that fits easily under a desk or can be conveniently wall-mounted, with quick access to all receptacles.
- Protects loads on six outlets - three with surge suppression and battery backup, three with surge suppression only.
- Keep essential systems running through power outages by plugging them into receptacles with surge suppression and battery backup. Plug non essential equipment into receptacles featuring surge suppression only.
- Extend UPS service life with user-replaceable batteries.
- Phone line transient protector guards phone equipment from "back door" power surges.
- Stay informed of power problems and low battery conditions with audible alarms and remote alarm notification.
- Deliver short-term mobile power with start-on-battery capability.
- USB port and cable are standard
- Rest easy with a two-year full warranty, plus three year pro-rated warranty and \$25,000 load protection guarantee (Australia and New Zealand). Optional Fastfix Service Plan is available to provide repair and replacement coverage that goes beyond the provision of the warranty.

In a perfect world, your incoming utility power would be smooth, steady and completely reliable. In the real world however, utility power is plagued with sags, surges and outages - some of them even caused by your equipment itself.

The risks are everywhere. Lightning strikes, storms, over-demand on the utility grid, accidents and natural disasters can knock out power without warning. Everyday events, such as normal utility switching or rapid changes in power demand can cause equipment-damaging surges or sags. A typical power customer experiences these events daily, as well as several complete outages a year.

Every time the lights dim when a major appliance starts up ... or a problem in the distribution grid causes a momentary loss of power ... or a surge travels

down the line when the power comes back up again ... your sensitive electronic equipment is being hit with electrical forces it was never designed to withstand. Even when these power fluctuations don't crash systems, or zap electronic components, they still cause insidious damage that can erode data integrity, damage important files and shorten hardware life.

You don't have to take it. Effective protection is here, at a very attractive price.

The Powerware 3105 UPS provides a layer of defence between your equipment and erratic power. This cost-effective, compact device stands guard constantly, ready to take over and switch to battery power any time it detects a problem with normal utility power.

# Technical Specifications

## POWERWARE 3105

Model Number	31050350A	31050500A	31050700A
Capacity	350VA/210W	500VA/300W	700VA/420W
Dimensions (mm) HxWxD	180x280x115	180x280x115	180x280x115
Unit Weight (kg)	4.5	5	6.5
Input Connection	1.8 metre line cord IEC to Australian 10Amp Plug		
Output Connection	6 Australian 10Amp Outlets (3 Battery Backup & Surge Protection, 3 Surge Protection only)		
<b>Operation</b>			
Input Voltage Range	0-300 VAC		
Output Voltage Range	Nominal -18% to +10%		
On Battery Output Voltage	Nominal -12% to +10%		
Frequency	50 Hz		
Lighting/Surge Protection	476 joules		
Safety	AS/NZS62040.1.1, AS/NZS60950, A-Tick		
EMI	AS/NZS62040.2, AS/NZSCISPR22, C-Tick		
Transfer Time to Battery/AC	2-6 msec. typical		
Battery Type	Sealed, maintenance free lead-acid battery		
Typical Backup Time	3 minutes at full rated load		
Internet/Phone/Fax Protection	RJ11		
Short Circuit Protection	Circuit Breaker		
Communication Port	USB		
<b>Environmental</b>			
Operation Temperature	0°C - 40°C		
Operation Relative Humidity	0 to 95% non condensing		
Storage Temperature	-15°C - 50°C		
Software	Powerware LanSafe Software is included free of charge		
Service Plans	Optional Extended Warranty and On Site Changeover service plans available		

### Battery Run Times (in minutes)

Model	Load (VA)							
	80	170	250	330	400	500	600	700
31050350A	30	11	6	3				
31050500A	43	17	11	6	4	3		
31050700A	53	30	14	9	7	6	4	3

This guide provides typical application information. Battery run times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

**HEAD OFFICE**  
Eaton Power Quality Pty Ltd  
10 Kent Road  
Mascot NSW 2020  
Phone: +61 2 9693 9333  
Fax: +61 2 8338 1159  
www.powerware.com.au

**SALES OFFICES**  
Queensland  
Phone: +61 7 3891 1211  
Fax: +61 7 3891 2492

Victoria  
Phone: + 61 3 9706 5662  
Fax: + 61 3 9794 9150

South Australia  
Phone: +61 8 8347 3622  
Fax: +61 8 8445 6328

Western Australia  
Phone: +61 8 9240 5655  
Fax: + 61 8 9240 5644

Auckland New Zealand  
Phone: + 64 9 273 3970  
Fax: +64 9 273 3980

Sales 1300 UPS UPS  
Service 1300 303 059

Powerware and ABM are trade names, trademarks and/or service marks of Eaton Power Quality Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.



# Powerware

© 2005 Eaton Corporation  
All Rights Reserved  
Printed in Australia